

HANDLE TAPE

BN 6482 HM



BN 6482 HM

HANDLE TAPE

High tensile strength mono-oriented polypropylene film with synthetic rubber based adhesive.

MAIN APPLICATIONS AND ADVICES FOR THE CORRECT TAPE USE

Handling system for plastic and carton packages of water bottles, beverages, tetra-brick and paper rolls. To be applied after film shrinkage.

TECHNICAL DATA

BACKING	Mono-oriented polypropylene film
COLOR	Clear
ADHESIVE	Synthetic rubber and resins
TOTAL THICKNESS	70 μ m (AFE A 4006-ED.9/79)
ADHESION TO STEEL	400 cN/cm (AFE A 4001-ED.10/87)
MD TENSILE STRENGTH	35 daN/25mm (AFE A 4004-ED.9/79)

WARRANTY

The tape can be stored for maximum 12 months from the date of production in dry conditions and in its original packaging. The material should be protected from extreme temperatures and direct sunlight. Once removed from its original packaging, the tape should be protected from dust and other impurities. Keep the rolls in horizontal position.

The technical information and data, recommendations, and other statements provided in this document are based on Novacel tapes tests or experience. It will be up to the user matching the product with the working process or surface. Novacel tapes will not be, at any rate, held responsible for not proper use. Warranty is limited to replacement of products that Novacel tapes proves to be defective and keeps out any other damages.

INTRAPAC IS EXCLUSIVE DISTRIBUTOR FOR NOVACEL TAPES



INTRAPAC S.A.R.L
Boulevard Heights - Dekwaneh, Lebanon
+9611500404 +9611486868
admin@intrapac.lb.com
www.intrapac.lb.com

